

# Bảng thông số sản phẩm

Thông số kỹ thuật



APC Smart-UPS C, Line Interactive, 1000VA, Rackmount 2U, 230V, 4x IEC C13 outlets, SmartConnect port, USB and Serial communication, AVR, Graphic LCD

SMC1000I-2UC

## Overview

**Presentation** Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

**Lead Time** Usually Ships within 2 Weeks

## Main

**Main Input Voltage** 230 V

**Other Input Voltage** 220 V  
240 V

**Main Output Voltage** 230 V

**Other Output Voltage** 220 V  
240 V

**Rated Power In W** 600 W

**Rated Power In Va** 1000 VA

**Product Or Component Type** Uninterruptible power supply (UPS)

**Input Connection Type** IEC 320 C14

**Output Connection Type** 4 IEC 320 C13  
2 IEC Jumpers

**Number Of Rack Unit** 2U

**Number Of Cables** 1

**Battery Type** Lead-acid battery

**Provided Equipment** Documentation CD  
Installation guide  
Rack mounting brackets  
USB cable

## Complementary


**Software Package** SmartConnect software for remote power monitoring feature availability varies by terms of use

## Batteries & Runtime

**Thời Gian Chạy** [View Runtime Graph](#)

**Hiệu Suất** [View Efficiency Graph](#)

**Extended Runtime** 0

Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	3 h
Number Of Battery Replacement Quantity	1
Battery Life	4...6 year(s)
Replacement Battery	<a href="#">APCRBC124</a> 
Battery Charger Power	72 W rated

## General

Number Of Power Module Filled Slots	0
Number Of Power Module Free Slots	0
Product Web Sub-Family	Cloud-enabled monitoring
Redundant	No

## Physical

Colour	Black
Height	8.6 cm
Width	43.2 cm
Depth	40.6 cm
Net Weight	20.52 kg
Mounting Location	Front
Mounting Preference	Lower
Mounting Mode	Rack-mounted
Two Post Mountable	1
Usb Compatible	Yes

## Input

Input Voltage Limits	170...300 V adjustable 180...287 V
Network Frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Harmonic Distortion	Less than 5 %
Maximum Configurable Power In Va	1000 VA
Maximum Configurable Power In W	600 W
Transfer Time	6 ms typical : 10 ms maximum
Ups Type	Line interactive
Wave Type	Sine wave
Output Frequency	50/60 Hz +/- 3 Hz sync to mains

## Conformance

<b>Product Certifications</b>	C-Tick CE GOST VDE
<b>Standards</b>	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

<b>Acoustic Level</b>	42 dBA
<b>Heat Dissipation</b>	46 Btu/h
<b>Operating Altitude</b>	0...10000 ft
<b>Ambient Air Temperature For Operation</b>	0...40 °C
<b>Ambient Air Temperature For Storage</b>	-15...45 °C
<b>Storage Altitude</b>	0.00...15240.00 m
<b>Relative Humidity</b>	0...95 %
<b>Storage Relative Humidity</b>	0...95 %

## Communications & Management

<b>Control Panel</b>	Multifunction LCD status and control console
<b>Free Slots</b>	0
<b>Communication Port Support</b>	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : configurable delays

## Surge Protection and Filtering

<b>Surge Energy Rate</b>	459 J
<b>Noise Suppression</b>	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	24.1 cm
<b>Package 1 Width</b>	58.4 cm
<b>Package 1 Length</b>	54.6 cm
<b>Package 1 Weight</b>	22.33 kg

## Contractual warranty

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------

## Bền vững

Nhãn **Green Premium™** là cam kết của Schneider Electric trong việc mang lại các sản phẩm với hiệu suất môi trường tốt nhất. Green Premium hứa hẹn tuân thủ các quy định mới nhất, minh bạch về tác động môi trường, cũng như các sản phẩm thông minh và ít CO<sub>2</sub>.

[Tìm hiểu thêm >](#)



Sử dụng hiệu quả năng lượng   Take-back   Minh bạch   RoHS/REACH

## Hiệu suất tài nguyên

Energy Efficient Product

Take-Back Program Available

## Hiệu suất sức khỏe

Mercury Free

Rohs Exemption Information   [Yes](#)

## Chứng nhận & Tiêu chuẩn

Reach Regulation   [REACH Declaration](#)

Eu Rohs Directive   Compliant  
[EU RoHS Declaration](#)

Environmental Disclosure   [Product Environmental Profile](#)

Circularity Profile   [End of Life Information](#)