

# Product datasheet

Specifications



## APC Smart-UPS On-Line, 3kVA, Tower, 230V, 8x C13+2x C19 IEC outlets, SmartSlot, Extended runtime, W/O rail kit

SRT3000XLI

### Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

### Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	2700 W
Rated power in VA	3000 VA
Input Connection Type	BS1363A British IEC 60320 C20 Schuko CEE 7 / EU1-16P
Output connection type	8 IEC 60320 C13 2 IEC Jumpers 2 IEC 60320 C19
Cable length	2.44 m
Number of cables	3
Battery type	Lead-acid battery
Provided equipment	CD with software Country-specific detachable power cord Documentation CD Installation guide Removable support feet USB cable Warranty card

### Batteries & Runtime

Battery recharge time	3 h
Number of battery replacement quantity	1
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Battery voltage	96 V
Battery charger power	168 W rated
Battery life	3...5 year(s)

---

Replacement battery	<a href="#">APCRBC152</a> 
---------------------	--

---

Extended runtime	1
------------------	---

---

## General

---

UPS type	Double conversion online
----------	--------------------------

---

Product web sub-family	High density
------------------------	--------------

---

Number of power module free slots	0
-----------------------------------	---

---

Number of power module filled slots	0
-------------------------------------	---

---

Redundant	No
-----------	----

---

## Physical

---

Colour	Black
--------	-------

---

Height	43.2 cm
--------	---------

---

Width	8.5 cm
-------	--------

---

Depth	63.5 cm
-------	---------

---

Net weight	31.3 kg
------------	---------

---

Mounting location	Front
-------------------	-------

---

Mounting preference	Lower
---------------------	-------

---

Mounting mode	Rack-mounted with kit
---------------	-----------------------

---

Two post mountable	0
--------------------	---

---

USB compatible	Yes
----------------	-----

---

Mounting position	Vertical
-------------------	----------

---

## Input

---

Network frequency	40...70 Hz auto-sensing
-------------------	-------------------------

---

Input voltage limits	100...275 V adjustable (half load)
----------------------	------------------------------------

---

## Output

---

Maximum configurable power in VA	3000 VA
----------------------------------	---------

---

Maximum configurable power in W	2700 W
---------------------------------	--------

---

Output frequency	50/60 Hz +/- 3 Hz sync to mains
------------------	---------------------------------

---

Wave type	Sine wave
-----------	-----------

---

Harmonic distortion	Less than 2 %
---------------------	---------------

---

Crest factor	3 : 1
--------------	-------

---

Bypass type	Internal bypass (automatic and manual)
-------------	--

---

## Conformance

---

Product certifications	CE EAC RCM VDE
------------------------	-------------------------

---

Marking	CE Mark
---------	---------

---

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	--

---

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...15240.00 m
Acoustic level	55 dBA
Heat dissipation	703 Btu/h
IP degree of protection	IP20

## Communications & Management

Free slots	1
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

## Surge Protection and Filtering

Surge energy rate	340 J
-------------------	-------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	40.000 cm
Package 1 Width	80.000 cm
Package 1 Length	120.000 cm
Package 1 Weight	48.640 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---

**Recommended replacement(s)**