

# Product datasheet

Specifications



## APC Easy UPS On-Line, 10kVA/ 10kW, Tower, 230V, Hard wire 3- wire(1P+N+E) outlet, Intelligent Card Slot, LCD

SRV10KI

### Overview

<b>Presentation</b>	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
<b>Lead Time</b>	Usually in Stock

### Main

<b>Main Input Voltage</b>	230 V
<b>Product Or Component Type</b>	Uninterruptible power supply (UPS)
<b>Other Input Voltage</b>	220 V 240 V
<b>Main Output Voltage</b>	230 V
<b>Other Output Voltage</b>	220 V 240 V
<b>Rated Power In W</b>	10000 W
<b>Rated Power In Va</b>	10000 VA
<b>Output Connector Type</b>	Hard wire 3-wire (1P + N + E) 1
<b>Provided Equipment</b>	1 USB cable 1 RS-232 configuration cable user manual

### Batteries & Runtime

<b>Run Time</b>	<a href="#">View Runtime Graph</a>
<b>Efficiency</b>	<a href="#">View Efficiency Graph</a>
<b>Battery Type</b>	Lead-acid battery
<b>Battery Voltage</b>	192 V
<b>Number Of Battery Filled Slots</b>	0
<b>Number Of Battery Free Slots</b>	0
<b>Battery Recharge Time</b>	5 h
<b>Battery Life</b>	3...5 year(s)
<b>Battery Charger Power</b>	235 W rated

### General

<b>Number Of Power Module Filled Slots</b>	0
<b>Number Of Power Module Free Slots</b>	0

Redundant	No
-----------	----

## Physical

Colour	Black (RAL 7010)
Height	68.5 cm
Width	19 cm
Depth	44.7 cm
Net Weight	65 kg
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Usb Compatible	Yes
Mounting Position	Vertical

## Input

Input Voltage Limits	110...300 V 60 % load 176...300 V full load
Number Of Input Connectors	1 hard wire 3-wire (1P + N + E)
Network Frequency	40...70 Hz auto sensing

## Output

Maximum Configurable Power In Va	10000 VA
Maximum Configurable Power In W	10000 W
Output Frequency	50/60 Hz +/- 3 Hz sync to mains
Harmonic Distortion	1 %
Ups Type	Double conversion online
Wave Type	Sine wave
Efficiency	94 % (full load)
Additional Information	Configurable for 220 : 230 or 240 nominal output voltage
Bypass Type	Internal bypass (automatic and manual)
Crest Factor	3 : 1

## Conformance

Product Certifications	CE UKCA EAC TISI
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...3000 m

Ambient Air Temperature For Storage	-15...60 °C
Storage Relative Humidity	0...95 % non-condensing
Storage Altitude	0...15000 m
Acoustic Level	58 dB
Heat Dissipation	2128 Btu/h
Ip Degree Of Protection	IP20

## Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency Power Off	Yes
Free Slots	1
Control Panel	Multifunction LCD status and control console

## Surge Protection and Filtering

Surge Energy Rate	600 J
-------------------	-------

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	91 cm
Package 1 Width	32 cm
Package 1 Length	58 cm
Package 1 Weight	77 kg

## Contractual warranty


Warranty	2 years repair or replace
----------	---------------------------

## Sustainability


**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)

## Well-being performance

 Mercury Free

---

 Rohs Exemption Information [Yes](#)

---

**Reach Regulation** [REACH Declaration](#)

---

**Eu Rohs Directive** Compliant with Exemptions

---