Product datasheet

Specifications





APC Easy UPS On-Line, 10kVA/ 10kW, Rackmount 4U, 230V, Hard wire 3-wire(1P+N+E) outlet, Intelligent Card Slot, LCD, W/ Rail Kit

SRV10KRIRK

Overview

Presentation	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
Lead Time	Usually in Stock
Main	
Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated Power In W	10000 W
Rated Power In Va	10000 VA
Output Connector Type	Hard wire 3-wire (1P + N + E) 1
Number Of Rack Unit	4U
Provided Equipment	1 USB cable 1 RS-232 configuration cable 2 rack mounting brackets 2 rack mounting support rails 1 external battery pack 1 battery cable user manual

Batteries & Runtime

Run Time	View Runtime Graph 🗗
Efficiency	View Efficiency Graph □
Battery Type	Lead-acid battery
Battery Voltage	192 V
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	5 h
Battery Life	35 year(s)
Battery Charger Power	235 W rated

General



Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number Of Power Module Filled Slots	0
Number Of Power Module Free Slots	0
Redundant	No

Physical

Colour	Black (RAL 7010)
Height	17.3 cm
Width	43.8 cm
Depth	71.0 cm
Net Weight	68 kg
Mounting Location	Front
Mounting Preference	Lower
Mounting Mode	Rack-mounted
Usb Compatible	Yes
Mounting Position	Horizontal

Input

Input Voltage Limits	110300 V 60 % load 176300 V full load
Number Of Input Connectors	1 hard wire 3-wire (1P + N + E)
Network Frequency	4070 Hz auto sensing

Output

Maximum Configurable Power In Va	10000 VA
Maximum Configurable Power In W	10000 W
Output Frequency	50/60 Hz +/- 3 Hz sync to mains
Harmonic Distortion	1 %
Ups Туре	Double conversion online
Wave Type	Sine wave
Efficiency	94 % (full load)
Bypass Type	Internal bypass (automatic and manual)
Crest Factor	3 : 1

Conformance

Product Certifications	CE UKCA EAC TISI
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient Air Temperature For Operation

Relative Humidity	095 % non-condensing
Operating Altitude	03000 m
Ambient Air Temperature For Storage	-1560 °C
Storage Relative Humidity	095 % non-condensing
Storage Altitude	015000 m
Acoustic Level	58 dBA
Heat Dissipation	2128 Btu/h
Ip Degree Of Protection	IP20

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency Power Off	Yes
Free Slots	1
Control Panel	Multifunction LCD status and control console

Surge Protection and Filtering

Surge Energy Rate 600 J

Packing Units

•	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	48.5 cm
Package 1 Width	83.6 cm
Package 1 Length	60 cm
Package 1 Weight	79 kg

Contractual warranty

Warranty

2 years repair or replace

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Learn more about Green Premium \geq



Transparency RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

