

# Eaton 9SX11KIPM

Catalog Number: 9SX11KIPM

Eaton 9SX Power Module, 11 kVA, 10 kW, Input: Hardwired, Outputs: Hardwired, Rack/tower, 3U

## General specifications



<b>Product Name</b>	Eaton 9SX UPS	<b>Catalog Number</b>	9SX11KIPM
<b>UPC</b>	743172039392	<b>Product Length/Depth</b>	70 cm
<b>Product Height</b>	44 cm	<b>Product Width</b>	13 cm
<b>Product Weight</b>	21 kg	<b>Warranty</b>	2 year
<b>Compliances</b>	CE Marked TUV cULus Listed CSA 22.2	<b>Certifications</b>	IEC/EN 62040-1 UL 1778 IEC/EN 62040-2 CE cULus Listed EAC

## Battery

### Runtime graph

View runtime graph

### Battery replacement

No battery

### Battery quantity

0

### Battery management

ABM & Temperature compensated charging method (user selectable)  
Automatic battery test  
Deep discharge protection  
Automatic recognition of external battery units

### Extended battery capability

Yes

## Electrical output

### Receptacle

Hardwired

### Voltage

230V

### Wattage

10 kW

### Output power factor

0.9

### Output voltage range

200/208/220/230/240/250 V +/- 1%

### Output waveform

Sine wave

### Output nominal voltage

230V default (200/208/220/230/240/250V)

### Voltage distortion output (linear load) - max

2

### Feed type

1

### Topology

Online/Double-conversion

### VA rating

11 kVA

## Electrical input

### Input connection

Hardwired/fixed connection

### Input nominal voltage

230V default (200/208/220/230/240/250V)

### Nominal frequency

50/60 Hz

### Input power factor

>.99

### Input voltage range

176-276 V (100-276 V with derating)

## Communications

### Includes network card

No

### Communication

USB port (HID compliant)

Serial port (RS232)

Mini terminal block for remote On/Off

Mini-terminal block for remote power off

Dry contacts (4 outputs, relay, DB9)

#### Input frequency range

40-70 Hz

#### Ethernet interface

No

#### User interface

Multilingual graphical LCD display

#### Potential free switch contact

Yes

#### Expansion slots

One slot for optional communication card

#### Software compatibility

Eaton Intelligent Power Manager, Eaton Intelligent Power Protector

#### Type of interface

Other

### Environmental

#### Altitude

3000 m

#### Noise level

<50 dB at 1 meter

#### Temperature range

0° to 40°C (32° to 104°F)

#### Relative humidity

0-95% non-condensing

### Additional specifications

#### Construction type

Free standing model

#### Package contents

Power Module  
USB cable  
Serial cable  
(2) Supports for tower mounting  
Safety instructions  
Quickstart guide

#### Phase (output)

1

#### Internal bypass

Yes

#### Auto shutdown function

Yes

#### Color

Black

#### Efficiency

95

#### Rack mounting kit

No

Phase (input)

1

Hot swap power

No

## Resources

### Brochures

[Eaton UPS Services Quick Guide 2021](#)

[Eaton UPS and battery services](#)

### Certification reports

[EC DoC Eaton 9SX](#)

### Manuals and user guides

[Eaton 9SX-9PX UPS - 8-11 kVA-EBM 240V - Installation and user manual](#)

### Technical data sheets

[Eaton 9SX UPS - 5/6/8/11 kVA - Datasheet](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2023 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)