

SANTAK TRUE ONLINE CASTLE SERIES UPS

CASTLEUPS

1 ~ 3kVA Power Management Expert





















AUTHORIZED EXPORTER & MASTER DISTRIBUTOR OF SANTAK UPS PRODUCTS IN VIET NAM ECOTEK CANADA PROMOTION TRADE CORPORATION

REGISTERED AND BUSINESS ADDRESS:

1188 West Georgia Street, Unit 1440, Vancouver, B.C, Canada, V6E 4A2

Co. Reg. No.: BC0895460

Web: www.ecotek-canada.vn



CONTACTS IN VIETNAM:

3/4 Nguyen Van Thu Str, Da Kao ward, District 1, Ho Chi Minh City, Vietnam

Phone: +84-904.204.849 (The North of Vietnam)

: +84-909.893.682 (The Central of Vietnam) : +84-909.892.447 (The South of Vietnam)

Email: vietnam@ecotek-canada.vn



Crucial moment, Powering your business

Santak UPS provide reliable protection for critical equipment and data

Higher power density, more power output

Wider input range, higher efficiency

Ultra low noise, multiple configurable options

High quality LCD with wide view

Product Introduction

C1-3K(S) is the leading double conversion topology on-line UPS from Santak. It inherits the high quality standard of the previous Castle series generations, and provides much stronger performance. It offers ideal solution for the major power quality problems such as grid power failure, under voltage, over voltage, sag, surge, line noise, frequency variation, switching transient, harmonic distortion efficiently, and provides a reliable power protection to the customer equipment.

Castle C1-3K(S) product provides high adaptability and flexible configuration, and it is applied with leading DSP control technology and offer multiple and extendable options to meet the increasing customized application demand.



C1-3kVA mainly applied in

• IT and network equipment

Small server or workstation Switches and monitoring system • MOEM and automatic control system

ATM, ticket machine Electrictiy and railway signal system SCADA system

· Office equipment

computer, printer scanner, POS equipment

Product performance

Safe and reliable

Best selling UPS and most widely installed on-line UPS, more than 30 years experience, perfectly match in mutiple utility environment

Professional digital control design technology, strong power semiconductors, Triple protection from hardware and firmware design, safer and more reliable

Green power design, energy saving

Output power factor up to 0.9, providing more power

High efficency design, save the operating cost, reduce the carbon emissions

Green and environment protection design, meet all strict standards


Easy use, Easy extension

Easy battery configuration and can meet different backup time requirement

Intelligent and real time battery monitoring

Multiple options, support different applications

★ Wide input voltage and frequency range



Grid power variation range

C1-3kVA wide input voltage and frequency range

comply with generator



Wide Input voltage range 115-300Vac

Adaptable to Harsh environment



Ultra-low noise <40 dB



Castle C1-3kVA is widely applied in different places

Harsh environmemt in high altitudes area

Remote area with poor grid power

Coastal area with high humidity and high temperature

Middle and big cities under power supply shortage pressure

C1-3kVA always provides safe and reliable protection to your equipment











Model		C1K-LCD	C1KS-LCD	C2K-LCD	C2KS-LCD	C3K-LCD	C3KS-LCD
Rating	VA/W	1000VA/900W 2000VA/1800W 3000VA/2700W				V2700W	
Input	Input Voltage Range	100~300 Vac					
	Frequency Range	40 Hz - 70 Hz					
	Input Wiring	Single phase with ground					
	Input power factor	0.99					
Output	Output Power Factor	0.9					
	Nominal Output Voltage	220/230/240 Vac					
	Voltage Regulation	1%					
	Frequency Range (Battery Mode)	50/60±0.05Hz					
	Outlet	IEC C13*4	IEC C13*3	IEC C13*4	IEC C13*6	IEC C13*4 IEC C19*1	IEC C13*3 Terminal Blocker*1
	Current Crest Ratio	3:1					
	Voltage Distortion (THDv)	< 1% @ linear load, < 5%@ non-linear load					
	Output Waveform	Pure sine wave					
Efficinecy	Inverter Mode	ир	up to 89% up to 91% up to 91%				to 91%
	ECO Mode	up to 97%					
Battery	Battery Type	12V / 9Ah	External batteries required	12V / 9Ah	External batteries required	12V / 9Ah	External batteries required
	Number of Internal Battery	2		4		6	
	Rated Battery Voltage	24V		48V		72V	
	Backup Time (@ FullLoad)	>3.5 mins	depends on customer configuration	>3.5 mins	depends on customer configuration	>3.5 mins	depends on customer configuration
	Recharge Time(to 90%)	4 hours		4 hours		4 hours	
	Charging Current	1.5A	6A	1.5A	6A	1.5A	6A
Transfer Time	Battery Mode<>InverterMode	0ms					
	Inverter Mode<>BypassMode	4ms (typical)					
Display	LCD	load rating / battery capacity / input / output / operating mode					
Dimension	WxHxD (mm)	144x228x356mm	102x228x346mm	190x327x399mm	102x327x390mm	190x327x399mm	102x327x390mm
Net Weight		9.2 kg	3.9 kg	17.4 kg	6.4 kg	22.7 kg	6.4 kg
Environment	Operating Temperature	0~40°C					
	Noise Level (1)	<40dB@1 meter					
Interface	RS232	Yes					
	Communication Slot	Yes, comply optional cards NMC, CMC, AS400 card					

Note: C1-3K(S)LCD-010124

(1) Noise level may vary with equipment, confuguation, temperature, etc.

- * All internal batteries are default as STK brand, any other battery brand might be appiled without prior notice.
- * Backup time is approximate and may vary with equipment, configuration, battery age, temperature, etc.
- * In the interests of continuous product improvement, all specifications are subject to change without notice.

AUTHORIZED EXPORTER & MASTER DISTRIBUTOR OF SANTAK UPS PRODUCTS IN VIET NAM



Ecotek Canada Promotion Trade Corporation

Address: 3/4 Nguyen Van Thu Str, DaKao ward, District 1, Ho Chi Minh City, Vietnam

Phone : +84-904.204.849 (The **North** of Vietnam)

: +84-909.893.682 (The **Central** of Vietnam) : +84-909.892.447 (The **South** of Vietnam)

Email : <u>vietnam@ecotek-canada.vn</u>

Web : <u>www.ecotek-canada.vn</u>





Technical supports provided by 64 Active Service Points (A.S.P)

licensed by ECOTEK-CANADA®

covering all 64 provinces and cities of Vietnam