

Product datasheet

Specifications



APC Easy UPS, 700VA, Tower, 230V, 2 Universal outlets, AVR, 1 USB Type A Port

BVX700LUI-MS

Overview

Lead time Usually in Stock

Main

Main Input Voltage	230 V AC 1 phase
Main Output Voltage	230 V AC 1 phase
Rated power in W	360 W
Rated power in VA	700 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 60320 C14
output connection type	2 universal
Cable length	1.2 m
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	User manual
Range of product	Easy UPS

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Battery voltage	12 V
Battery capacity	7.0 Ah
Battery life	2...3 year(s)
Replacement battery	APCRBC110
Extended runtime	0

General

Max runtime	120 min
Number of power module free slots	0

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of power module filled slots	0
Redundant	No
UPS size	WS

Physical

Colour	Black
Height	13.8 cm
Width	9.8 cm
Depth	31 cm
Net weight	4.2 kg
Mounting support	Floor
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	170...280 V 230 V AC
Cos phi	0.51

Output

Maximum configurable power in W	360 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Full load runtime	00:00:01 360 W
Graph display	1
Half load runtime	00:06:00 180 W
Maximum configurable power in VA	700 VA
Transfer time	6 ms typical : 10 ms maximum

Conformance

Product certifications	CE CB
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m

Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...3000 m
Acoustic level	40 dBA
IP degree of protection	IP20

Surge Protection and Filtering

Surge energy rate	273 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22.2 cm
Package 1 Width	34.6 cm
Package 1 Length	14.2 cm
Package 1 Weight	4.5 kg
SCC14	10731304417610

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant

SCIP Number

E7333b0a-8d2c-4a40-a279-6eb5db3419eb

REACH Regulation

[REACH Declaration](#)

Use Again

Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Removable battery

User replaceable

Take-back

No

WEEE

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins